

POWER2RAXX LL 80

The modular commercial storage unit



E-Mobility



Drive
System



Energy Storage
Systems



Power- and
Garden Tools



Industrial



Medical

BMZ POWER2RAXX LL 80

Long life energy storage system for commercial and industrial applications

POWER2RAXX LL 80 The indoor and outdoor solution

- Robust storage system, flexibly adaptable Compact and scalable, consisting of 80,9 kWh units
- Durable, robust & safe
- Up to 10 POWER2RAXX LL 80 can be connected together to form a battery system



TECHNICAL DETAILS

Basic parameters	Indoor	Outdoor
Energy (max.)*	80.9 kWh	80.9 kWh
Nominal voltage	409 V	409 V
Capacity (max.)	198 Ah	198 Ah
Charging current (max.)	90 A	90 A
Discharge current – peak (3s)	100 A	100 A
Discharge current (nom.)	90 A	90 A
Discharge power (max.)	40 kW	40 kW
Discharge power – peak	50 kW	50 kW
Cycles	up to 10,000	Up to 10,000
Optional PV (max.)	60 kWp	60 kWp
Optional PV input current (max.)	4 MPPTs, each 30A	4 MPPTs, each 30A

*According to IEC 0.1 C, charge to 4.2 V, discharge to 2.5 V with 0.1 C at 25 °C.

Basic parameters	Indoor	Outdoor
Optional PV-MP PT voltage range	200-850 V	200-850 V
Nominal AC voltage	3L/N/PE; 220/380V; 230/400V; 240/415V	3L/N/PE; 220/380V; 230/400V; 240/415V
Max. output AC current	60 A	60 A
UPS switching time	< 20 ms	< 20 ms
Operating ambient temperature	0 to 45 °C	-10 bis +60 °C
Enclosure protection class	IP21	IP55
Max. weight single rack single inverter	798 kg 75 kg	812 kg 75 kg
Dimensions (W x H x D) single rack single inverter	816 x 2131 x 839 800 x 620 x 300	816 x 2131 x 839 800 x 620 x 300
Communication interfaces	CAN / RS-485 / Ethernet	CAN / RS-485 / Ethernet
Certifications	CE / UN38.3 / EN61439	CE / UN38.3 / EN61439
Areas of application	On Grid / On Grid +Backup Off Grid	On Grid / On Grid +Backup Off Grid

Modul Type	Helios VE LongLife
Cell type	Li-Ion - BMZ Technology
Dimensions (W x H x D)	217 mm x 155 mm x 546 mm
Weight	22 kg
Voltage	50.4 V
Capacity	66 Ah

Any questions?

Contact us, we will be pleased to advise you.

HEADQUARTERS

BMZ Germany GmbH
Zeche Gustav 1
63791 Karlstein am Main
Deutschland

T: +49 6188 9956 0
E: mail@bmz-group.com

BMZ USA Inc.

1429 Miller Store Road
Virginia Beach
VA 23455
USA

T: +1-757 821 8494
E: contact.usa@bmz-group.com

BMZ Company Ltd.

Julong Technology Building B
Cuibao Road, Longgang District,
Shenzhen, Guangdong Province
P.R.China 518116

T: +86 755 8977 5800
E: contact.china@bmz-group.com

BMZ France S.A.R.L.

16 Rue Auber
75009 Paris
Frankreich

T: +33 06 84 52 76 29
E: contact.france@bmz-group.com

BMZ Japan KK

Shitaya 1-6-5, Taito-ku,
Tokyo, 110-0004
Japan

T: +81 35811 1973
E: contact.japan@bmz-group.com

BMZ Poland Sp. z o.o.

Alberta Einsteina 9
44-109 Gliwice
Polen

T: +48 327842 450
E: contact.poland@bmz-group.com

BMZ Innovation Group Ltd

Future Business Centre
Kings Hedges Road
Cambridge, CB4 2HY
United Kingdom

T: +44 7767 038663
E: contact.uk@bmz-group.com

BMZ Brazil

Rua de Rocha Pombo, 2561
Módulo 10A
São José dos Pinhais - Paraná
Brazil

T: +55 11 94463-0325
E: contact.brazil@bmz-group.com

BMZ DOOEL Ilinden

St. 106, Block 5
TIRZ Skopje 2 – Bunardzik
1000 Ilinden
North Macedonia

T: +389 70 229 670
E: contact.northmacedonia@bmz-group.com

www.bmz-group.com

© BMZ 2025

All rights reserved. Preliminary data sheet. Although great care has been taken in the preparation of this data sheet, BMZ accepts no responsibility for any errors or omissions. All information contained herein is subject to change without notice.

Stand: 11.2025/V1

